

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017 & ANSI/NCSL Z540-1-1994

NOVAMED INC. 8136 N Lawndale Ave. Skokie, IL 60076

Mike Kahn Phone: 847 675 3550

CALIBRATION

Valid To: November 30, 2022 Certificate Number: 3053.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following calibrations^{1, 4}:

I. Mechanical

Parameter/Equipment	Range	CMC ² (±)	Comments
Volume ³ — Pipettes Burettes, Dispensers, Cylinders, Syringes	(0.1 to 2) μL (2 to 10) μL (10 to 20) μL (20 to 100) μL (100 to 200) μL (200 to 1000) μL (1000 to 5000) μL (5000 to 10 000) μL (10 000 to 20 000) μL (20 000 to 50 000) μL (50 000 to 100 000) μL	0.011 μL 0.048 μL 0.041 μL 0.15 μL 0.31 μL 1.4 μL 5.8 μL 16 μL 29 μL 44 μL 120 μL	Gravimetric method using mass balance
Scales and Balances ³	0.1 mg to 1 g (1 to 5) g (5 to 20) g (20 to 50) g (50 to 100) g (100 to 150) g (150 to 210) g (1 to 100) g (100 to 500) g (500 to 1000) g (1000 to 2000) g (2000 to 10 000) g (10 000 to 30 000) g	0.09 mg 0.09 mg 0.11 mg 0.15 mg 0.20 mg 0.32 mg 0.36 mg 2.9 mg 11 mg 21 mg 52 mg 110 mg 260 mg	ASTM E-E898, NIST Handbook-44, ASTM-Class 1, ASTM-Class 2, ASTM-Class 4, OIML-Class F2

(A2LA Cert. No. 3053.01) 11/20/2020

¹ This laboratory offers commercial calibration service and field calibration service.

hu

² Calibration and Measurement Capability Uncertainty (CMC) is the smallest uncertainty of measurement that a laboratory can achieve within its scope of accreditation when performing more or less routine calibrations of nearly ideal measurement standards or nearly ideal measuring equipment. CMCs represent expanded uncertainties expressed at approximately the 95 % level of confidence, usually using a coverage factor of k = 2. The actual measurement uncertainty of a specific calibration performed by the laboratory may be greater than the CMC due to the behavior of the customer's device and to influences from the circumstances of the specific calibration.

³ Field calibration service is available for this calibration and this laboratory meets A2LA *R104* – *General Requirements: Accreditation of Field Testing and Field Calibration Laboratories* for these calibrations (in both the US and Canada). Please note the actual measurement uncertainties achievable on a customer's site can normally be expected to be larger than the CMC found on the A2LA Scope. Allowance must be made for aspects such as the environment at the place of calibration and for other possible adverse effects such as those caused by transportation of the calibration equipment. The usual allowance for the actual uncertainty introduced by the item being calibrated, (e.g. resolution) must also be considered and this, on its own, could result in the actual measurement uncertainty achievable on a customer's site being larger than the CMC.

⁴This scope meets A2LA's *P112 Flexible Scope Policy*.



Accredited Laboratory

A2LA has accredited

NOVAMED INC.

Skokie, IL

for technical competence in the field of

Calibration

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This laboratory also meets the requirements of ANSI/NCSL Z540-1-1994 and R205 – Specific Requirements: Calibration Laboratory Accreditation Program. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

SEAL 1978 SEAL 1978 A2LA

Presented this 20th day of November 2020.

Vice President, Accreditation Services

For the Accreditation Council

Certificate Number 3053.01

Valid to November 30, 2022